

NX3600

Multi-Spindle
WINDING MACHINE
Series



NX3600 Series Automation Coil Winder

FEATURE

1. Programing feature for various winding design (Windows PC interface provides easy operation.)
 - Easy program building by the online programming system.
 - Variable pitch, variable speed, progressive winding and such high performance programs available.
 - Support, program and run all same programing commands in your current TANAC coil winders.
2. Heavy duty stand alone base unit design for high speed and layer winding.
3. Easy maintenance design by the trouble information display in the screen with sensor conditions.
4. Fully automation design with the TANAC tool transferring system (Optional)
5. Available various optional devices as the nipper unit, the wire skeiner, the taper unit, the loading/un-loading device, tensioners, the safety shield and so on.

SPECIFICATION

	NX3604	NX3606	NX3608	NX3612
Number of Spindles	4	6	8	12
Maximum Spindle Speed	4,000 / 10,000 / 16,000 [rpm]			
Spindle Pitch [mm]	90	60	45	30
Wire Size [mm]	0.02-0.60	0.02-0.45	0.02-0.40	0.02-0.30
Wrapping Device Movement	X: 100, Y: 100, Z: 70 [mm]			
Power	AC 200-230 [V] 50Hz/60Hz (Shingle Phase +/-10%)			
Consumption	1500 [W]			
Air Pressure	0.49-0.59 [MPa]			
Dimensions	800 (W) x 1300 (D) x 1200 (H) [mm]			
Weight	300 [kg]			

●The picture in the another side is the image photograph as in the production line. Tensioners and some other optional items are not including in the original coil winder.

●We have various optional devices as the air nipper unit, the wire skeiner unit, the loading/un-loading device, tensioners, the safety shield ...etc. Please contact and ask for them to sales office near your place.

●Because of improvement, the specifications are subject to change without notice.



TNK CO., LTD.

TANAC, INC.

<http://www.tnk-ltd.com/>

CA0035A07E